




TYPE APPROVAL CERTIFICATE
No. ELE037718XT/027

This is to certify that the product below is found to be in compliance with the applicable requirement of the RINA type approval system.

<i>Description</i>	ELECTRIC CABLES
<i>Type</i>	FMGCH 150/250 V
<i>Applicant</i>	2M KABLO SAN. VE TIC. A.S. GAZIOSMANPASA OSB MAH., 4.CADDE, No.18A CERKEZKOY 59500 Tekirdag TURKEY
<i>Manufacturer</i>	2M KABLO SAN. VE TIC. A.S.
<i>Place of manufacture</i>	GAZIOSMANPASA OSB MAH., 4.CADDE, No.18A CERKEZKOY 59500 Tekirdag TURKEY
<i>Reference standards</i>	IEC 60092-350; IEC 60092-376.

Issued in **ISTANBUL** on **March 29, 2019**. This Certificate is valid until **August 19, 2023**



RINA Services S.p.A.
Cinar Kutlar

This certificate consists of this page and 1 enclosure



TYPE APPROVAL CERTIFICATE

No. ELE037718XT/027

Enclosure - Page 1 of 1

FMGCH 150/250 V

Materials/Components

Shipboard instrumentation, control and communication cables, flame retardant, halogen free with low smoke emission, for ships and off-shore units installation.

Rated voltage: 150 / 250 V

Maximum rated conductor temperature: + 85 °C

Type: FMGCH

Marking: 2MKABLO IEC 60092-376 FMGCH n x m x s(mm²) 150/250 V IEC 60332-3-22 [METER MARK]

Construction

Conductor: Stranded Electrolytic Annealed Copper Class 2

Insulation: HEPR

Lay-Up: Pairs/triples/quads are stranded in layers

Screen: Electrolytic Copper Wire Braiding

Outer Sheath: HFFR SHF1

Number of Units: 1, 2, 3, 4, 5, 6, 7, 8, 10, 12, 14, 16, 18, 19, 20, 24, 28, 30, 37, 44, 60 Cross-sec. area of conductors 0,5 to 2,5 mm²

Reference documents: Technical Specification No: 111-3/2011 (16/03/2012)

Reference Standards: IEC 60092-350; IEC 60092-376; IEC 60332-3-22; IEC 60332-1-2; IEC 60228; IEC 60811; IEC 60754-1; IEC 60754-2; IEC 60092-360; IEC 60684-2; IEC 61034-1/2; IEC60754-1/2

ISTANBUL March 29, 2019