

**TYPE APPROVAL CERTIFICATE****This is to certify:****That the Electric Power Cable**with type designation(s)  
**M2X 0,6/1 kV Switchboard wire**

Issued to

**2M Kablo Sanayi ve Ticaret A.S**  
**TEKİRDAĞ, Turkey**

is found to comply with

**DNV GL rules for classification – Ships, offshore units, and high speed and light craft**  
**DNV GL class programme DNVGL-CP-0399 – Type approval – Electric cables****Application :****Product approved by this certificate is accepted for installation on all vessels classed by DNV GL.****Rated voltage (kV) 0,6/1**  
**Temp. class (°C) 90**Issued at **Høvik** on **2019-09-18**This Certificate is valid until **2021-10-10**.DNV GL local station: **Istanbul**Approval Engineer: **Georgiy Abramenko**for **DNV GL**

---

**Trond Sjøvåg**  
**Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-031245-1**  
 Certificate No: **TAE000019U**  
 Revision No: **1**

## Product description

Type: M2X 0,6/1 kV Switchboard wire

Construction:

Conductor: Plain or Tinned, stranded copper class 2 or class 5

Core insulation: HF90

No of cores:	Cross sectional area [mm <sup>2</sup> ]
1	1 – 300

## Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

## Type Approval documentation


### Tests carried out

Standard	Release	General description	Limitation
IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	
IEC 60092-353	2016-09	Electrical installations in ships - Part 353: Power cables for rated voltages 1 kV and 3 kV	0,6/1 kV
IEC 60332-3-22	2018-07	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	Bunch test Category A
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables - Part 1: Determination of the halogen acid gas content	Low Halogen: <0,5% Halogen
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS/mm
IEC 61034-1/2	2013-07 2013-09	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke Light transmittance ≥60%
IEC 60684-2	2011-08	Flexible insulating sleeving – Part 2: Methods of test Clause 45.2 Methods of determination of low levels of fluorine	HF max 0,1% [0,02% can be detected]

## Marking of product

2M Kable – M2X – Size – 0,6/1 kV – IEC 60332 Cat. A – Lot no.

## Periodical assessment



Job Id: **262.1-031245-1**  
Certificate No: **TAE000019U**  
Revision No: **1**

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE