

**TYPE APPROVAL CERTIFICATE**  
No. ELE037718XT/024

**This is to certify** that the product below is found to be in compliance with the applicable requirement of the RINA type approval system.


<i>Description</i>	<b>ELECTRIC CABLES</b>
<i>Type</i>	<b>FM2XCH 150/250 V</b>
<i>Applicant</i>	<b>2M KABLO SAN. VE TIC. A.S. GAZIOSMANPASA OSB MAH., 4.CADDE, No.18A CERKEZKOY 59500 Tekirdag TURKEY</b>
<i>Manufacturer</i>	<b>2M KABLO SAN. VE TIC. A.S.</b>
<i>Place of manufacture</i>	<b>GAZIOSMANPASA OSB MAH., 4.CADDE, No.18A CERKEZKOY 59500 Tekirdag TURKEY</b>
<i>Reference standards</i>	<b>IEC 60092-350; IEC 60092-376.</b>

Issued in **ISTANBUL** on **March 29, 2019**. This Certificate is valid until **August 19, 2023**



RINA Services S.p.A.  
**Cinar Kutlar**

This certificate consists of this page and 1 enclosure



## TYPE APPROVAL CERTIFICATE

No. ELE037718XT/024

Enclosure - Page 1 of 1

FM2XCH 150/250 V

### Materials/Components

Shipboard instrumentation, control and communication cables, flame retardant, halogen free with low smoke emission, for ships and off-shore units installation.

Rated voltage: 150 / 250 V

Maximum rated conductor temperature: + 85 °C

Type: FM2XCH

Marking: 2MKABLO IEC 60092-376 FM2XCH n x m x s(mm<sup>2</sup>) 150/250 V IEC 60332-3-22 [METER MARK]

### Construction

Conductor: Stranded Electrolytic Annealed Copper Class 2

Insulation: XLPE

Lay-Up: Pairs and quads are stranded in layers

Screen: Electrolytic Copper Wire Braiding

Outer Sheath: HFFR SHF1

Number of Units: 1, 2, 4, 5, 7, 8, 10, 12, 14, 16, 18, 19, 20, 24, 37 Cross-sectional area of conductors 0,5 and 0,75 mm<sup>2</sup>

Reference documents: Technical Specification No: 107-3/2011 (15/03/2012)

Reference Standards: IEC 60092-350; IEC 60092-376; IEC 60332-3-22; IEC 60332-1-2; IEC 60228; IEC 60811; IEC 60754-1; IEC 60754-2; IEC 60092-360; IEC 60684-2; IEC 61034-1/2; IEC60754-1/2

**ISTANBUL March 29, 2019**