


## HSLH-JZ



### Areas of Use

These types of HFFR cables are used in office equipment, electronic control systems, air condition systems, power stations, engineering projects for control, vision and measurement purposes. These can be used in wet or dry indoor applications. Because of the HFFR material, These don't burn easily and when These do, the flames go off by themselves. These have low smoke density and These don't emit poisonous and corrosive gases during a fire. These used in buildings where there are important goods or human population.

### Cable Construction

<b>Conductor</b>	Stranded Annealed Copper (IEC/EN 60228, Class 5)
<b>Insulation</b>	HFFR (EN 50290-2-26)
<b>Core Colors</b>	Black (white numbered) Green-Yellow earth core in the outer layer (3 cores and above)
<b>Lay-up</b>	Cores are stranded in layers
<b>Outer Sheath</b>	HFFR (EN 50290-2-27), RAL 7001 - Grey
<b>Reference Standards</b>	TS 13734

### Technical Properties

<b>Operating Voltage</b>	0.50 mm <sup>2</sup> .. 1.50 mm <sup>2</sup> 300 V / 500 V; 2.50 mm <sup>2</sup> ..... 450 V / 750 V
<b>Test Voltage</b>	2500 V
<b>Conductor Resistance</b>	0.50 mm <sup>2</sup> - ≤39 Ω/km; 0.75 mm <sup>2</sup> - ≤26 Ω/km; 1.00 mm <sup>2</sup> - ≤19.5 Ω/km; 1.50 mm <sup>2</sup> - ≤13.3 Ω/km; 2.50 mm <sup>2</sup> - ≤7.98 Ω/km
<b>Insulation Resistance</b>	>200 M.Ωxkm
<b>Temperature Range</b>	Fixed: -30 °C .....+70 °C, Flexible: -5 °C .....+70 °C
<b>Smoke Density</b>	IEC/EN 61034-2
<b>Amount of Halogen Acid Gas</b>	IEC/EN 60754-1
<b>Corrosive Gases Measurement</b>	IEC/EN 60754-2
<b>Min. Bending Radius</b>	Fixed: 8 x Cable Diameter, Flexible: 15 x Cable Diameter

### Cross Section

Configuration / Cross-Section (mm/mm <sup>2</sup> )	Cable Diameter (mm) (± 5%)	Copper Weight (kg / km)	~ Cable Weight (kg / km)
3x1	6.0	25	68
3x1.5	7.0	38	93
3x2.5	8.2	62	137
5x1	7.1	42	108
5x1.5	9.0	64	141
5x2.5	10.4	105	213
7x1	7.8	59	130
7x1.5	9.5	89	182
7x2.5	11.3	146	273

12x1	11.0	103	231
12x1.5	13.0	153	323
12x2.5	14.8	252	428
18x1	12.5	155	327
18x1.5	15.0	235	458
18x2.5	17.4	378	622
24x1	14.8	208	455
24x1.5	17.9	307	557

**18.01.2025 20:59**

**Legal Warning:** The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.

If you need more information about the products in this catalog, please contact us via [info@2mkablo.com](mailto:info@2mkablo.com) or call +90 (212) 222 8250.