LIHCH



Areas of Use

These screened cables are used as signal transmission cables for indoor applications. These can be easily used with their flexible construction in narrow applications like electronic control systems of computer or audio systems or communication sector, electronic circuits, measurement devices, machine design, office equipment, etc. Screening protects the cable from the outer electrical effects. These cables have HFFR material in their construction and These don't burn easily and if these do the flames go off by themselves. These have low smoke density and These don't emit poisonous and corrosive gases during the fire. These used in buildings where there are important goods or human population.

Cable Construction

Conductor	Stranded Annealed Copper (IEC/EN 60228, Class 5, 0.34 mm²: Class 2)
Insulation	HFFR (EN 50290-2-26)
Core Colors	DIN 47100 (4 cores colors, white, yellow, brown, green)
Lay-up	Cores are stranded in layers
Separator	PET Foil
Screen	Tinned Copper Wire Braid
Outer Sheath	HFFR (EN 50290-2-27), RAL 7001 - Grey
Reference Standards	VDE 0812, TS 13755
CPR Classes	B2ca s1a d1 a1

Technical Properties

Operating Voltage	0.14 mm²..0.25 mm² 250 V; 0.34 mm²..1.50 mm² 300 V / 500 V; 2.50 mm²..... 450 V / 750 V
Test Voltage	0.14 mm² - 800 V; 0.22 mm² ....1.00 mm²- 1200 V; 1.50 mm²..... 2.50 mm² - 2500 V
Conductor Resistance	0.14 mm²- ≤138 Ω/km; 0.22 mm²- ≤85 Ω/km; 0.25 mm²- ≤77.8 Ω/km; 0.34 mm²- ≤56 Ω/km; 0.50 mm²- ≤39 Ω/km; 0.75 mm²- ≤26Ω/km; 1.00 mm²- ≤19.5 Ω/km; 1.50 mm²- ≤13.3 Ω/km; 2.50 mm²- ≤7.98 Ω/km
Insulation Resistance	>200 M.Ωxkm
Capacitance (@800Hz)	Core - Core: 0.14 mm²-≤80 nF/km; 0.22 mm²..0.34 mm²-≤100 nF/km; 0.50 mm²..0.75 mm²-≤110 nF/km; 1.00 mm²..1.50 mm²-≤120nF/km; 2.50 mm²- ≤140 nF/km Core-Screen: 0.14 mm²-≤120 nF/km; 0.22 mm²..0.34 mm²-≤150 nF/km; 0.50 mm²..0.75 mm²-≤170 nF/km; 1.00 mm²..1.50 mm²-≤180nF/km; 2.50 mm²- ≤240 nF/km
Indutance (approx.)	0.65 mH/km
Temperature Range	Fixed: -30 °C .....+70 °C, Flexible: -5 °C .....+70 °C
Flame Retardancy	IEC/EN 60332-1
Smoke Density	IEC/EN 61034-2
Amount of Halogen Acid Gas	IEC/EN 60754-1
Corrosive Gases Measurement	IEC/EN 60754-2
Min. Bending Radius	Fixed: 8 x Cable Diameter, Flexible: 15 x Cable Diameter

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice.This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.
If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.