


## LIYY



### Areas of Use

These PVC cables are used in industrial applications for signal transmission. These can be easily used with their flexible construction in narrow applications like electronic control systems of computer or audio systems or communication sector, electronic circuits, measurement devices, machine design, office equipment, etc. These for indoor applications.

### Cable Construction

<b>Conductor</b>	Stranded Annealed Copper (IEC/EN 60228, Class 5, 0.34 mm <sup>2</sup> : Class 2)
<b>Insulation</b>	PVC (EN 50290-2-21)
<b>Core Colors</b>	DIN 47100 (4 cores colors, white, yellow, brown, green)
<b>Lay-up</b>	Cores are stranded in layers
<b>Outer Sheath</b>	PVC (EN 50290-2-22), RAL 7001 - Grey
<b>Reference Standards</b>	VDE 0812, TS 13755

### Technical Properties

<b>Operating Voltage</b>	0.14 mm <sup>2</sup> ..0.25 mm <sup>2</sup> 250 V; 0.34 mm <sup>2</sup> ..1.50 mm <sup>2</sup> 300 V / 500 V; 2.50 mm <sup>2</sup> ..... 450 V / 750 V
<b>Test Voltage</b>	0.14 mm <sup>2</sup> - 800 V; 0.22 mm <sup>2</sup> ....1.00 mm <sup>2</sup> - 1200 V; 1.50 mm <sup>2</sup> ..... 2.50 mm <sup>2</sup> - 2500 V
<b>Conductor Resistance</b>	0.14 mm <sup>2</sup> - ≤138 Ω/km; 0.22 mm <sup>2</sup> - ≤85 Ω/km; 0.25 mm <sup>2</sup> - ≤77.8 Ω/km;0.34 mm <sup>2</sup> - ≤56 Ω/km; 0.50 mm <sup>2</sup> - ≤39 Ω/km; 0.75 mm <sup>2</sup> - ≤26 Ω/km; 1.00 mm <sup>2</sup> - ≤19.5 Ω/km; 1.50 mm <sup>2</sup> - ≤13.3 Ω/km
<b>Insulation Resistance</b>	>200 M.Ωxkm
<b>Capacitance (@800Hz)</b>	Core - Core: 0.14 mm <sup>2</sup> -≤80 nF/km; 0.22 mm <sup>2</sup> ..0.34 mm <sup>2</sup> -≤100 nF/km; 0.50 mm <sup>2</sup> ..0.75 mm <sup>2</sup> -≤110 nF/km; 1.00 mm <sup>2</sup> ..1.50 mm <sup>2</sup> -≤120nF/km; 2.50 mm <sup>2</sup> - ≤140 nF/km
<b>Indutance (approx.)</b>	0.65 mH/km
<b>Temperature Range</b>	Fixed: -30 °C .....+70 °C, Flexible: -5 °C .....+70 °C
<b>Flame Retardancy</b>	IEC/EN 60332-1
<b>Min. Bending Radius</b>	Fixed: 8 x Cable Diameter, Flexible: 15 x Cable Diameter

### Cross Section

Configuration / Cross-Section (mm/mm <sup>2</sup> )	Cable Diameter (mm) (± 5%)	Copper Weight (kg / km)	~ Cable Weight (kg / km)
2x0.5	4.4	9	27
3x0.5	4.7	13	34
4x0.5	5.2	17	44
5x0.5	5.7	22	57
7x0.5	6.3	30	71
9x0.5	7.6	39	98

10x0.5	8.3	43	106
14x0.5	9.1	61	145
16x0.5	9.7	70	164
20x0.5	10.8	87	198
25x0.5	12.3	109	251
2x0.75	5.0	13	35
3x0.75	5.3	20	46
4x0.75	5.8	26	57
5x0.75	6.5	33	76
7x0.75	7.2	46	95
9x0.75	8.6	59	130
10x0.75	9.4	65	141
14x0.75	10.4	91	196
16x0.75	11.1	104	222
18x0.75	11.7	117	244
20x0.75	12.5	130	271
25x0.75	13.9	163	333
2x1	5.4	17	43
3x1	5.6	26	54
4x1	6.2	35	70
5x1	6.9	43	92
7x1	7.7	61	116
9x1	9.1	78	158
10x1	10.0	87	171
14x1	11.1	122	237
16x1	11.8	139	269
18x1	12.5	156	296
20x1	13.2	174	329
25x1	14.8	217	404
2x1.5	6.4	26	61
3x1.5	6.8	39	81
4x1.5	7.6	52	104
5x1.5	8.4	65	137
7x1.5	9.3	91	171
9x1.5	11.1	117	235
10x1.5	12.3	130	259
14x1.5	13.5	182	352
16x1.5	14.3	208	398
20x1.5	15.9	260	479
25x1.5	17.9	325	596
2x2.5	7.5	43	89
3x2.5	7.9	65	117
4x2.5	8.9	87	154
5x2.5	9.8	108	201

22.12.2024 22:32

**Legal Warning:** The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.  
If you need more information about the products in this catalog, please contact us via [info@2mkablo.com](mailto:info@2mkablo.com) or call +90 (212) 222 8250.