


LI2Y(St)CH -PiMF (RS - 485)



Areas of Use

Used in industrial automation systems for computer networks and electronic control systems for data transmission. Provides longer transmission lengths and larger data rates compared to RS 232-422. HFFR versions are less flammable in case of fire, mostly self-extinguishing, have low smoke density and they do not emit poisonous and corrosive gasses during a fire.

Cable Construction

Conductor	0.22 mm ² Stranded Tinned Copper (7x0.20 mm AWG 24), 0.34 mm ² Stranded Tinned Copper (7x0.25 mm AWG 22)
Insulation	PE (EN 50290-2-23, VDE 0207-2Y11)
Separator	PET Foil
1. Screen	Al-PET Foil (with stranded tinned copper drain wire)
Lay-up	All shielded pairs are stranded in layers
2. Screen	Al-PET Foil
3. Screen	Tinned Copper Wire Braid
Outer Sheath	HFFR (EN 50290-2-27), RAL 7001 - Grey
Core Colors	DIN 47100

Technical Properties

Operating Voltage	300 V
Test Voltage	1200 V
Velocity of Propagation	0,66
Insulation Resistance	>5000 M.Ωxkm
Capacitance (@800Hz)	Core - Core: ≤45 nF/km, Core - Cores - Screen: ≤80 nF/km
Characteristic Impedance	120±10 Ω
Loop Resistance	AWG 24: ≤182 Ω/km; AWG 22: ≤115 Ω/km; AWG 20: ≤72 Ω/km
Temperature Range	-30 °C.....+70 °C
Flame Retardancy	IEC/EN 60332-1
Smoke Density	IEC/EN 61034-1
Amount of Halogen Acid Gas	IEC/EN 60754-1
Corrosive Gases Measurement	IEC/EN 60754-2
Min. Bending Radius (Fixed)	10 x Cable Diameter

Cross Section

Configuration / Cross-Section (mm/mm ²)	Cable Diameter (mm) (± 5%)	Copper Weight (kg / km)	~ Cable Weight (kg / km)
2x2x0.22	8.9	38	83
3x2x0.22	9.4	47	103

4x2x0.22	10.4	56	127
2x2x0.34	9.4	45	96
3x2x0.34	10.0	56	116
4x2x0.34	11.1	68	145

03.05.2026 8:35

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.
If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.