


FireKab LIH(St)H FE180 PH120



Areas of Use

FireKab fire resistant cables are used for fire alarm systems, power supply or control of equipment that needs to function during a fire such as warning, emergency lighting, evacuation and monitor systems. The place of usage is intelligent or semi-intelligent buildings where dense human population or valuable goods are found. These can be hospitals, cinemas, theatres, schools, shopping centers, airports, factories, etc. FireKab products have low smoke density, are halogen-free and they don't emit poisonous gases.

Cable Construction

Conductor	Stranded Annealed Copper (IEC/EN 60228, Class 5, 0.34 mm ² : Class 2)
Insulation	Fire Resistant Silicon Rubber (EN 50363-1, BS 7655 E12)
Core Colors	DIN 47100 (4 cores colors, white, yellow, brown, green, for more than 5 cores white core-black numbered)
Lay-up	Cores are stranded in layers
Flame Barrier	Fiber Glass Tape
Screen	Al-PET Foil + Stranded Tinned Copper Drain Wire
Outer Sheath	HFFR (EN 50290-2-27), RAL 2004 - Orange (other colors upon request)
Reference Standards	TS 13734

Technical Properties

Operating Voltage	300 V / 500 V
Test Voltage	2000 V
Conductor Resistance	0.50 mm ² - ≤39 Ω/km; 0.75 mm ² - ≤26 Ω/km; 1.00 mm ² - ≤19.5 Ω/km; 1.50 mm ² - ≤13.3 Ω/km; 2.50 mm ² - ≤7.98 Ω/km
Insulation Resistance	>200 M.Ωxkm
Flame Retardancy	IEC/EN 60332-1, IEC/EN 60332-3-24
Fire Resistance	IEC 60331-21, EN 50200 PH120
Smoke Density	IEC/EN 61034-2
Amount of Halogen Acid Gas	IEC/EN 60754-1
Corrosive Gases Measurement	IEC/EN 60754-2
Min. Bending Radius	Fixed: 7.5 x Cable Diameter, Flexible: 15 x Cable Diameter
Temperature Range	-30 °C.....+70 °C, Flexible: -5 °C+60 °C

Cross Section

Configuration / Cross-Section (mm/mm ²)	Cable Diameter (mm) (± 5%)	Copper Weight (kg / km)	~ Cable Weight (kg / km)
2x0.5	4.7	12	34
3x0.5	4.8	16	41
4x0.5	5.4	20	51
5x0.5	6.0	25	66

7x0.5	6.5	34	78
10x0.5	8.5	43	114
2x0.75	5.2	19	44
3x0.75	5.5	25	55
4x0.75	6.1	32	69
5x0.75	6.7	38	87
7x0.75	7.4	52	108
10x0.75	9.7	72	156
2x1	5.5	23	52
3x1	5.8	32	63
4x1	6.4	40	80
5x1	7.1	50	102
7x1	7.8	68	126
10x1	10.3	94	187
2x1.5	6.7	32	73
3x1.5	7.0	46	90
4x1.5	7.7	57	114
5x1.5	8.6	72	146
7x1.5	9.4	98	183
9x1.5	11.3	124	247
10x1.5	12.5	137	271

24.04.2025 12:07

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract. If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.