


FireKab LIHH-TP FE180 PH120



Areas of Use

FireKab fire resistant cables are used for fire alarm systems, power supply or control of equipment that needs to function during a fire such as warning, emergency lighting, evacuation and monitor systems. The place of usage is intelligent or semi-intelligent buildings where dense human population or valuable goods are found. These can be hospitals, cinemas, theatres, schools, shopping centers, airports, factories, etc. FireKab products have low smoke density, are halogen-free and they don't emit poisonous gases.

Cable Construction

| | |
|----------------------------|----------------------------------------------------------------------------------|
| Conductor | Stranded Annealed Copper (IEC/EN 60228, Class 5, 0.34 mm ² : Class 2) |
| Insulation | Fire Resistant Silicon Rubber (EN 50363-1, BS 7655 E12) |
| Core Colors | DIN 47100 (for more than 2 pairs black-white / numbered) |
| Lay-up | Cores are twisted as pairs and pairs are stranded in layers |
| Flame Barrier | Fiber Glass Tape |
| Outer Sheath | HFFR (EN 50290-2-27), RAL 2004 - Orange (other colors upon request) |
| Reference Standards | TS 13734 |

Technical Properties

| | |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Voltage | 300 V / 500 V |
| Test Voltage | 2000 V |
| Conductor Resistance | 0.50 mm ² - ≤39 Ω/km; 0.75 mm ² - ≤26 Ω/km; 1.00 mm ² - ≤19.5 Ω/km; 1.50 mm ² - ≤13.3 Ω/km; 2.50 mm ² - ≤7.98 Ω/km |
| Insulation Resistance | >200 M.Ωxkm |
| Flame Retardancy | IEC/EN 60332-1, IEC/EN 60332-3-24 |
| Fire Resistance | IEC 60331-21, EN 50200 PH120 |
| Smoke Density | IEC/EN 61034-2 |
| Amount of Halogen Acid Gas | IEC/EN 60754-1 |
| Corrosive Gases Measurement | IEC/EN 60754-2 |
| Min. Bending Radius | Fixed: 7.5 x Cable Diameter, Flexible: 15 x Cable Diameter |
| Temperature Range | -30 °C.....+70 °C, Flexible: -5 °C+60 °C |

Cross Section

| Configuration / Cross-Section (mm/mm ²) | Cable Diameter (mm) (± 5%) | Copper Weight (kg / km) | ~ Cable Weight (kg / km) |
|-----------------------------------------------------|----------------------------|-------------------------|--------------------------|
| 2x2x0.5 | 7.5 | 18 | 64 |
| 3x2x0.5 | 8.0 | 27 | 82 |
| 4x2x0.5 | 8.8 | 36 | 102 |
| 5x2x0.5 | 9.7 | 45 | 124 |
| 7x2x0.5 | 10.8 | 63 | 165 |
| 10x2x0.5 | 14.0 | 89 | 243 |

| | | | |
|-----------|------|-----|-----|
| 2x2x0.75 | 8.4 | 27 | 81 |
| 3x2x0.75 | 9.0 | 40 | 106 |
| 4x2x0.75 | 10.0 | 54 | 136 |
| 5x2x0.75 | 11.0 | 67 | 166 |
| 7x2x0.75 | 12.2 | 93 | 218 |
| 10x2x0.75 | 15.8 | 132 | 319 |
| 2x2x1 | 8.9 | 37 | 96 |
| 3x2x1 | 9.6 | 54 | 126 |
| 4x2x1 | 10.5 | 71 | 160 |
| 5x2x1 | 11.7 | 87 | 197 |
| 7x2x1 | 12.9 | 124 | 260 |
| 10x2x1 | 16.8 | 176 | 382 |
| 2x2x1.5 | 10.7 | 54 | 141 |
| 3x2x1.5 | 11.5 | 80 | 184 |
| 4x2x1.5 | 12.8 | 106 | 235 |
| 5x2x1.5 | 14.1 | 132 | 286 |
| 7x2x1.5 | 15.5 | 184 | 377 |
| 10x2x1.5 | 20.1 | 262 | 551 |

12.03.2025 22:59

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.

If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.