


## JE-Y(St)Y...Bd



### Areas of Use

These installation cables according to VDE 0815 with electrostatic screen for industrial electronics are used telecommunication, measurement and information/data process systems.

### Cable Construction

<b>Conductor</b>	Annealed Solid Copper (IEC/EN 60228)
<b>Insulation</b>	PVC (EN 50290-2-21 T11, VDE 0207 Part 4 Y11)
<b>Core Colors</b>	TS 13767, VDE 0815
<b>Lay-up</b>	5 star quads laid up to a bundle, bundles laid up in layers
<b>Separator</b>	PET Foil
<b>Drain Wire</b>	Solid Tinned Copper Wire
<b>Screen</b>	Al-PET Foil
<b>Outer Sheath</b>	PVC (EN 50290-2-22 TM1, VDE 0207 Part 5 YM1), RAL 7032 - Grey
<b>Reference Standards</b>	TS 13767, VDE 0815

### Technical Properties

<b>Operating Voltage</b>	300 V
<b>Test Voltage</b>	800 V
<b>Insulation Resistance</b>	>100 M.Ωxkm
<b>Capacitance (@800Hz)</b>	≤ 100 nF/km (capacitance values may increase by 20% up to 4 pair)
<b>Loop Resistance</b>	≤ 73.2 Ω/km
<b>Temperature Range</b>	-30 °C.....+70 °C
<b>Flame Retardancy</b>	IEC/EN 60332-1
<b>Min. Bending Radius (Fixed)</b>	8 x Cable Diameter

### Cross Section

Configuration / Cross-Section (mm/mm <sup>2</sup> )	Cable Diameter (mm) (± 5%)	Copper Weight (kg / km)	~ Cable Weight (kg / km)
2x2x0.8 + 0.8	5.6	25	61
4x2x0.8 + 0.8	7.7	45	103
8x2x0.8 + 0.8	12.2	86	187
16x2x0.8 + 0.8	15.2	167	331
20x2x0.8 + 0.8	16.7	207	398
32x2x0.8 + 0.8	21.3	328	619
40x2x0.8 + 0.8	23.3	409	771

**23.04.2026 12:52**

**Legal Warning:** The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.

If you need more information about the products in this catalog, please contact us via [info@2mkablo.com](mailto:info@2mkablo.com) or call +90 (212) 222 8250.