RE-2Y(St)YSWAY(ö)



Areas of Use

Used for communication and instrumentation purposes in industries like oil exploration, cement, paper, steel, power generation as well as in intrinsically safe systems in hazardous areas like petrochemical plants and thermal power plants to monitor measuring equipment in process automation applications. Armoured types provide mechanical strength and protect the cable core against outer mechanical effects. Additional oil and hydrocarbon resistance are achieved by its special design.

Cable Construction

Conductor	Stranded Annealed Copper (IEC/EN 60228, Class 2)
Insulation	PE (EN 50290-2-23)
Core Colors	Multicore: White Numbered Pair: Black / White, Numbered Triples: Balck / White / Red, Numbered Quad: Black / White / Red / Blue, Numbered
Separator	PET Foil
Overall Screen	Al-PET Foil (with 7x0.3 mm Tinned Copper Drain Wire)
Inner Sheath	PVC (EN 50290-2-22)
Armour	Round Galvanized Steel Wire (Min. Diameter 0.90 mm ±0.02 mm)
Outer Sheath	UV Resisdant, Flame Retardant, Oil and Aliphatic Hydrocarbon Resistant, NBR/PVC, RAL 9005 - Black, RAL 5015 - Blue (other colors upon request)
Reference Standards	BS/EN 50288-7
Lay-up	Cores / pairs / triples / quads are stranded in layers

Technical Properties

Operating Voltage	500 V*
Test Voltage	Core - Core: 2000 V; Core - Screen: 1000 V
Conductor Resistance	0.50 mm² - ≤36 Ω/km; 0.75 mm² - ≤24.5 Ω/km; 1.00 mm² - ≤18.1 Ω/km; 1.30 mm² - ≤14.2 Ω/km; 1.50 mm² - ≤12.1 Ω/km; 2.50 mm² - ≤7.41 Ω/km
Insulation Resistance	>5000 M.Ωxkm
Capacitance Unbalance (800 Hz)	≤500 pF/500m
Capacitance (@800Hz)	≤85 nF/km (Capacitance values may increase by 20% up to 4 pairs)
L/R Ratio	0.50 mm²..1.00 mm² - ≤25 µH/Ω; 1.30 mm²..1.50 mm² - ≤40 µH/Ω; 2.50 mm² - ≤60 µH/Ω
Temperature Range	Fixed: -40 °C .....+70 °C, Flexible: -5 °C .....+50 °C
Flame Retardancy	IEC/EN 60332-1, IEC/EN 60332-3-24 (CAT C)
Oil Resistance	IEC/EN 60811-404 ASTM No 2 oil 90 °C 168 hours (7x24)
Aliphatic Hydrocarbon Resistant	NF M 87-202
Min. Bending Radius (Fixed)	12 x Cable Diameter

03.11.2026 9:03

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice.This catalog

is only a guide and is valid at the time of download, not valid for an offer or contract.
If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.