


RE-Y(St)YSWAY(ö)



Areas of Use

Used for communication and instrumentation purposes in industries like oil exploration, cement, paper, steel, power generation as well as in intrinsically safe systems in hazardous areas like petrochemical plants and thermal power plants to monitor measuring equipment in process automation applications. Armoured types provide mechanical strength and protect the cable core against outer mechanical effects. Additional oil and hydrocarbon resistance are achieved by its special design.

Cable Construction

| | |
|----------------------------|--|
| Conductor | Stranded Annealed Copper (IEC/EN 60228, Class 2) |
| Insulation | PVC (EN 50290-2-21) |
| Core Colors | Multicore: White Numbered Pair: Black / White, Numbered Triples: Black / White / Red, Numbered Quad: Black / White / Red / Blue, Numbered |
| Lay-up | Cores / pairs / triples / quads are stranded in layers |
| Separator | PET Foil |
| Overall Screen | Al-PET Foil (with 7x0.3 mm Tinned Copper Drain Wire) |
| Inner Sheath | PVC (EN 50290-2-22) |
| Armour | Round Galvanized Steel Wire (Min. Diameter 0.90 mm ±0.02 mm) |
| Outer Sheath | UV Resistant, Flame Retardant, Oil and Aliphatic Hydrocarbon Resistant, NBR/PVC, RAL 9005 - Black, RAL 5015 - Blue (other colors upon request) |
| Reference Standards | BS/EN 50288-7 |

Technical Properties

| | |
|--|--|
| Operating Voltage | 500 V* |
| Test Voltage | Core - Core: 2000 V; Core - Screen: 1000 V |
| Conductor Resistance | 0.50 mm ² - ≤36 Ω/km; 0.75 mm ² - ≤24.5 Ω/km; 1.00 mm ² - ≤18.1 Ω/km; 1.30 mm ² - ≤14.2 Ω/km; 1.50 mm ² - ≤12.1 Ω/km; 2.50 mm ² - ≤7.41 Ω/km |
| Capacitance Unbalance (800 Hz) | ≤500 pF/500m |
| Capacitance (@800Hz) | ≤170 nF/km (Capacitance values may increase by 20% up to 4 pairs) |
| L/R Ratio | 0.50 mm ² ..1.00 mm ² - ≤25 μH/Ω; 1.30 mm ² ..1.50 mm ² - ≤40 μH/Ω; 2.50 mm ² - ≤60 μH/Ω |
| Temperature Range | Fixed: -40 °C+70 °C, Flexible: -5 °C+50 °C |
| Flame Retardancy | IEC/EN 60332-1, IEC/EN 60332-3-24 (CAT C) |
| Oil Resistance | IEC/EN 60811-404 ASTM No 2 oil 90 °C 168 hours (7x24) |
| Aliphatic Hydrocarbon Resistant | NF M 87-202 |
| Min. Bending Radius (Fixed) | 12 x Cable Diameter |
| Insulation Resistance | >10 M.Ωxkm |

Cross Section

| Configuration / Cross-Section (mm/mm ²) | Cable Diameter (mm) (± 5%) | Copper Weight (kg / km) | ~ Cable Weight (kg / km) |
|---|----------------------------|-------------------------|--------------------------|
|---|----------------------------|-------------------------|--------------------------|

| | | | |
|-----------|------|-----|------|
| 1x2x0.5 | 10.2 | 14 | 235 |
| 2x2x0.5 | 13.0 | 24 | 344 |
| 3x2x0.5 | 13.5 | 33 | 379 |
| 4x2x0.5 | 14.5 | 43 | 432 |
| 5x2x0.5 | 15.4 | 53 | 484 |
| 6x2x0.5 | 16.5 | 62 | 540 |
| 7x2x0.5 | 16.5 | 72 | 557 |
| 8x2x0.5 | 18.1 | 81 | 639 |
| 10x2x0.5 | 20.8 | 100 | 879 |
| 12x2x0.5 | 21.4 | 120 | 947 |
| 14x2x0.5 | 22.3 | 139 | 1022 |
| 16x2x0.5 | 23.3 | 158 | 1100 |
| 18x2x0.5 | 24.3 | 177 | 1188 |
| 20x2x0.5 | 25.6 | 196 | 1286 |
| 24x2x0.5 | 28.4 | 234 | 1625 |
| 30x2x0.5 | 29.9 | 292 | 1817 |
| 1x2x0.75 | 10.7 | 19 | 253 |
| 2x2x0.75 | 13.9 | 34 | 387 |
| 3x2x0.75 | 14.6 | 48 | 433 |
| 4x2x0.75 | 15.6 | 63 | 496 |
| 5x2x0.75 | 16.7 | 78 | 560 |
| 6x2x0.75 | 17.9 | 92 | 631 |
| 7x2x0.75 | 17.9 | 107 | 654 |
| 8x2x0.75 | 20.4 | 121 | 871 |
| 10x2x0.75 | 22.7 | 150 | 1029 |
| 12x2x0.75 | 23.3 | 179 | 1102 |
| 14x2x0.75 | 24.3 | 208 | 1202 |
| 16x2x0.75 | 25.5 | 238 | 1313 |
| 18x2x0.75 | 27.3 | 267 | 1554 |
| 20x2x0.75 | 28.5 | 296 | 1677 |
| 24x2x0.75 | 31.5 | 354 | 1985 |
| 30x2x0.75 | 34.0 | 441 | 2463 |
| 1x2x1 | 11.0 | 24 | 268 |
| 2x2x1 | 14.5 | 44 | 420 |
| 3x2x1 | 15.1 | 64 | 471 |
| 4x2x1 | 16.3 | 83 | 544 |
| 5x2x1 | 17.5 | 103 | 621 |
| 6x2x1 | 18.8 | 123 | 701 |
| 7x2x1 | 18.8 | 142 | 730 |
| 8x2x1 | 21.5 | 162 | 963 |
| 10x2x1 | 23.8 | 201 | 1140 |
| 12x2x1 | 24.4 | 241 | 1230 |
| 14x2x1 | 25.6 | 280 | 1351 |
| 16x2x1 | 27.4 | 319 | 1603 |
| 18x2x1 | 28.7 | 359 | 1746 |
| 20x2x1 | 30.1 | 398 | 1884 |

| | | | |
|----------|------|-----|------|
| 24x2x1 | 34.0 | 477 | 2468 |
| 30x2x1 | 35.7 | 594 | 2775 |
| 1x2x1.3 | 11.5 | 30 | 294 |
| 2x2x1.3 | 15.1 | 56 | 455 |
| 3x2x1.3 | 16.0 | 81 | 526 |
| 4x2x1.3 | 17.2 | 107 | 604 |
| 5x2x1.3 | 18.4 | 132 | 685 |
| 6x2x1.3 | 20.5 | 158 | 901 |
| 7x2x1.3 | 20.5 | 183 | 937 |
| 8x2x1.3 | 22.7 | 209 | 1085 |
| 10x2x1.3 | 25.3 | 260 | 1286 |
| 12x2x1.3 | 26.0 | 311 | 1391 |
| 14x2x1.3 | 27.7 | 362 | 1663 |
| 16x2x1.3 | 29.1 | 413 | 1819 |
| 18x2x1.3 | 30.4 | 464 | 1956 |
| 20x2x1.3 | 32.2 | 515 | 2176 |
| 24x2x1.3 | 36.1 | 617 | 2769 |
| 30x2x1.3 | 38.2 | 771 | 3144 |
| 1x2x1.5 | 11.8 | 33 | 308 |
| 2x2x1.5 | 15.6 | 62 | 481 |
| 3x2x1.5 | 16.4 | 91 | 547 |
| 4x2x1.5 | 17.7 | 120 | 640 |
| 5x2x1.5 | 19.0 | 148 | 725 |
| 6x2x1.5 | 21.2 | 177 | 963 |
| 7x2x1.5 | 21.2 | 206 | 1002 |
| 8x2x1.5 | 23.4 | 235 | 1140 |
| 10x2x1.5 | 26.0 | 292 | 1356 |
| 12x2x1.5 | 27.4 | 350 | 1612 |
| 14x2x1.5 | 28.7 | 407 | 1773 |
| 16x2x1.5 | 30.0 | 465 | 1917 |
| 18x2x1.5 | 31.7 | 522 | 2142 |
| 20x2x1.5 | 34.1 | 580 | 2560 |
| 24x2x1.5 | 37.3 | 695 | 2952 |
| 30x2x1.5 | 39.3 | 867 | 3330 |
| 1x2x2.5 | 13.1 | 51 | 372 |
| 2x2x2.5 | 17.8 | 97 | 608 |
| 3x2x2.5 | 18.8 | 144 | 705 |
| 4x2x2.5 | 21.2 | 190 | 961 |
| 5x2x2.5 | 22.7 | 236 | 1098 |
| 6x2x2.5 | 24.5 | 283 | 1253 |
| 7x2x2.5 | 24.5 | 329 | 1315 |
| 8x2x2.5 | 27.8 | 375 | 1640 |
| 10x2x2.5 | 31.0 | 468 | 1962 |
| 12x2x2.5 | 32.2 | 560 | 2187 |
| 14x2x2.5 | 34.6 | 653 | 2682 |
| 16x2x2.5 | 36.3 | 746 | 2913 |

| | | | |
|----------|------|------|------|
| 18x2x2.5 | 38.2 | 838 | 3184 |
| 20x2x2.5 | 40.1 | 931 | 3451 |
| 24x2x2.5 | 45.1 | 1116 | 4438 |
| 30x2x2.5 | 47.7 | 1394 | 5043 |

23.02.2025 5:35

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.
If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.