

## FM2XAACH FE180



### Areas of Use

Used for communication and instrumentation purpose in electronic systems of marine vehicles. Screening layer protects the transmitting signal against electromagnetic interferences. Halogen-Free and Flame Retardant construction ensure non-corrosive and highly visible environment during a fire. Also, min. 180 minutes of circuit integrity under fire conditions is achieved by its special design.

### Cable Construction

<b>Conductor</b>	Stranded Annealed Copper (IEC/EN 60228, Class 2) (tinned copper and/or Class 5 versions are available upon request)
<b>Flame Barrier</b>	Mica Tape
<b>Insulation</b>	XLPE (IEC 60092-360)
<b>Core Colors</b>	Pair: Black / White, Numbered Quad: Black / White / Red / Blue, Numbered
<b>1. Separator</b>	PET Foil
<b>Individual Screen</b>	Al-PET Foil (with Tinned Copper Drain Wire)
<b>2. Separator</b>	PET Foil
<b>Lay-up</b>	Shielded pairs / triples are stranded in layers
<b>Separator</b>	PET Foil
<b>1. Overall Screen</b>	Al-PET Foil (with Tinned Copper Drain Wire)
<b>Separator</b>	PET Foil (HFFR filler upon request)
<b>2. Overall Screen</b>	Annealed Copper Wire Braid (90% Coverage)
<b>Outer Sheath</b>	HFFR (IEC 60092-360 SHF1), RAL 6018 - Green
<b>Reference Standards</b>	IEC 60092-376

### Technical Properties

<b>Operating Voltage</b>	150/250 (300) V
<b>Test Voltage</b>	1.5 kV (a.c) 3.6 kV (d.c)
<b>Conductor Resistance</b>	IEC/EN 60228
<b>Insulation Resistance</b>	>5000 M.Ωxkm
<b>Temperature Range</b>	-40 °C.....+90 °C
<b>Flame Retardancy</b>	IEC/EN 60332-1-2, IEC/EN 60332-3-22 (CAT A)
<b>Fire Resistance</b>	IEC 60331-21
<b>Smoke Density</b>	IEC/EN 61034-1+2
<b>Amount of Halogen Acid Gas</b>	IEC/EN 60754-1
<b>Corrosive Gases Measurement</b>	IEC/EN 60754-2
<b>Min. Bending Radius (Fixed)</b>	8 x Cable Diameter

23.02.2025 5:53

**Legal Warning:** The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.  
If you need more information about the products in this catalog, please contact us via [info@2mkablo.com](mailto:info@2mkablo.com) or call +90 (212) 222 8250.