
FM2XASH



Areas of Use

Used for communication and instrumentation purpose in electronic systems of marine vehicles. Screening layer protects the transmitting signal against electromagnetic interferences. Halogen-Free and Flame Retardant construction ensure non-corrosive and highly visible environment during a fire.

Cable Construction

Conductor	Stranded Annealed Copper (IEC/EN 60228, Class 2) (tinned copper and/or Class 5 versions are available upon request)
Insulation	XLPE (IEC 60092-360)
Core Colors	Pair: Black / White, Numbered Quad: Black / White / Red / Blue, Numbered
Lay-up	Cores / pairs / triples / quads are stranded in layers
Separator	PET Foil
Overall Screen	Al-PET Foil (with Tinned Copper Drain Wire)
Inner Sheath	HFFR
Armour	Galvanised Steel Wire Braid
Outer Sheath	HFFR (IEC 60092-360 SHF1), RAL 9005 - Black or RAL 7001 - Grey
Reference Standards	IEC 60092-376

Technical Properties

Operating Voltage	150/250 (300) V
Test Voltage	1.5 kV (a.c) 3.6 kV (d.c)
Conductor Resistance	IEC/EN 60228
Insulation Resistance	>5000 M.Ωxkm
Temperature Range	-40 °C.....+90 °C
Flame Retardancy	IEC/EN 60332-1-2, IEC/EN 60332-3-22 (CAT A)
Smoke Density	IEC/EN 61034-1+2
Amount of Halogen Acid Gas	IEC/EN 60754-1
Corrosive Gases Measurement	IEC/EN 60754-2
Min. Bending Radius (Fixed)	8 x Cable Diameter

03.11.2026 8:58

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice.This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.
If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.