M2X

Areas of Use

Used as fixed installation cable in marine vehicles. Halogen-Free and Flame Retardant construction ensures non-corrosive and highly visible environment during a fire.

Cable Construction

Conductor	Stranded Annealed Copper (IEC/EN 60228, Class 5) (tinned copper and/or Class 2 versions are available upon request)
Insulation	XL HFFR (IEC 60092-360 HF90), Standard Outer Sheath: Black (other colors and double sheath upon request)
Reference Standards	IEC 60092-353

Technical Properties

Operating Voltage	0.6/1 (1.2) kV
Test Voltage	3.5 kV (a.c.) 8.4 kV (d.c)
Conductor Resistance	IEC/EN 60228
Insulation Resistance	>4000 M.Ω x km
Temperature Range	-40 °C.....+90 °C
Flame Retardancy	IEC/EN 60332-1-2, IEC/EN 60332-3-22 (CAT A)
Smoke Density	IEC/EN 61034-1+2
Amount of Halogen Acid Gas	IEC/EN 60754-1
Corrosive Gases Measurement	IEC/EN 60754-2
Min. Bending Radius (Fixed)	4 x Cable Diameter

09.10.2026 20:27

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice.This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.
If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.