

MGH



Areas of Use

Used as fixed installation cable in marine vehicles. Halogen-Free and Flame Retardant construction ensure non-corrosive and highly visible environment during a fire.

Cable Construction

Insulation	HEPR (IEC 60092-360)
Core Colors	According to HD 308 S2 (# of Cores ≥ 5 => White numbered)
Separator	PET Foil (HFFR filler upon request)
Outer Sheath	HFFR (IEC 60092-360 SHF1), RAL 9005 - Black or RAL 7001 - Grey
Reference Standards	IEC 60092-353
Conductor	Stranded Annealed Tinned Copper (IEC 60228, Class 2)

Technical Properties

Operating Voltage	0.6/1 (1.2) kV
Test Voltage	3.5 kV (a.c.) 8.4 kV (d.c)
Conductor Resistance	IEC/EN 60228
Insulation Resistance	>5000 M. Ω xkm
Temperature Range	-40 °C.....+90 °C
Flame Retardancy	IEC/EN 60332-1-2, IEC/EN 60332-3-22 (CAT A)
Smoke Density	IEC/EN 61034-1+2
Amount of Halogen Acid Gas	IEC/EN 60754-1
Corrosive Gases Measurement	IEC/EN 60754-2
Min. Bending Radius (Fixed)	6 x Cable Diameter

12.07.2026 0:33

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.

If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.