


NYBY



Areas of Use

0.6/1 kV, galvanized steel tape armoured power cables are used in generally underground where high tensile stresses and mechanical protection are needed during the operation. These are resistant to increasing operating temperature in the short term.

Cable Construction

| | |
|----------------------------|---|
| Conductor | Solid or Stranded Annealed Copper (IEC/EN 60228, Class 1 / Class 2) |
| Insulation | PVC |
| Core Colors | HD 308 S2 |
| Filler | PVC |
| Armour | Galvanised Steel Tape |
| Outer Sheath | PVC |
| Reference Standards | TS IEC 60502-1, DIN VDE 0271 |

Technical Properties

| | |
|-----------------------------------|--|
| Operating Voltage | 0.6/1 kV |
| Test Voltage | 3.5 kV |
| Max. Operating Temperature | 70 °C |
| Flame Retardancy | IEC/EN 60332-1-2 |
| Min. Bending Radius | Single Core: 15 x Cable Diameter, Multicore: 12 x Cable Diameter |

21.06.2026 2:39

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.

If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.