


NYCY



Areas of Use

0.6/1 kV power cables with copper concentric conductors and tape are used in outdoor and underground applications. The concentric conductor can be used as neutral, protective or earth and connection monitoring the impacts on the cable through a control switch or a relay.

Cable Construction

Conductor	Solid or Stranded Annealed Copper (IEC/EN 60228, Class 1 / Class 2)
Insulation	PVC
Core Colors	HD 308 S2
Filler	PVC
Concentric Conductor	Copper Wire and Copper Tape
Outer Sheath	PVC
Reference Standards	TS IEC 60502-1, DIN VDE 0276-603

Technical Properties

Operating Voltage	0.6/1 kV
Test Voltage	3.5 kV
Max. Operating Temperature	70 °C
Flame Retardancy	IEC/EN 60332-1-2
Min. Bending Radius	Single Core: 15 x Cable Diameter, Multicore: 12 x Cable Diameter

21.11.2024 18:33

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.

If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.